



## DURON™ GEO LD 15W-40 NATURAL GAS MOBILE ENGINE OIL

### Introduction

DURON GEO Long Drain (LD) 15W-40 natural gas mobile engine oil delivers superior engine protection and extended drain\* capabilities for Compressed Natural Gas/Liquefied Natural Gas (CNG/LNG) engines in mobile applications. Specifically designed for extended drain intervals up to 1200 hours while protecting critical engine parts, DURON GEO LD 15W-40 can help minimize downtime and service costs by keeping fleets on the road longer. In addition to extended oil drains, DURON GEO LD 15W-40's proven technology helps CNG/LNG engines start with ease in cold weather, while retaining protection under high temperature operating conditions. With DURON GEO LD 15W-40's best-in-class all-weather protection, you can rest assured your engines will perform the way they were meant to while protecting critical engine parts.

Made with base oils that are 99.9% pure and blended with proven premium additives, DURON GEO LD 15W-40 outperforms demanding OEM specifications such as Cummins CES 20074 and Detroit Diesel 93K216.

### Features and Benefits

- **Extended Drains\***
  - Extending oil drains up to 1200 hours can help minimize downtime, maintenance costs and waste to the environment
- **Less Oil Consumption**
  - Low volatility base oils decrease vapourization so less oil is lost, efficiency is improved, and the oil retains more of its fresh oil properties
  - Reduces oil top-up frequency

- **Advanced Engine Protection**

- Ultra pure, consistent quality base oils help minimize engine sludge and deposits, thereby maintaining excellent engine condition
- Protection and performance that exceed the expectations of the leading OEMs
- Optimized oil ash content to suit engine operating conditions

- **Better Low Temperature Pumpability**

- Exceptional cold start protection
- Excellent low temperature pumpability to protect equipment

- **Better Shear Stability**

- High Viscosity Index (V.I.) base oils and shear stable viscosity modifier help maintain oil viscosity for reduced engine wear and improved engine protection over the life of the oil

- **Better Resistance to Corrosion**

- Helps maintain engine performance and efficiency

- **Better Resistance to Oxidative Thickening**

- Helps maintain peak fuel economy
- Enables extended drain intervals
- Ensures continued low temperature protection

### Applications

DURON GEO LD 15W-40 is recommended for use in natural gas fuelled engines – CNG/LNG – in mobile applications that require excellent wear control.

#### What is the HT difference?

Petro-Canada starts with the HT purity process to produce water-white, 99.9% pure base oils. The result is a range of lubricants, specialty fluids and greases that deliver maximum performance for our customers.



\*Extending drain intervals should always be undertaken in conjunction with a regular oil analysis program. Refer to owner's manual or operations and maintenance manual for complete information.

## Approvals and Recommendations

■ Approved

Approvals	DURON GEO LD 15W-40
CUMMINS	
CUMMINS CES 20074	■
Detroit Diesel	
Detroit Diesel 93K216	■

## Typical Performance Data

PROPERTY	ASTM TEST METHOD	DURON GEO LD 15W-40
Kinematic Viscosity, cSt @ 40 °C	D445	115.2
Kinematic Viscosity, cSt @ 100 °C		15.4
Viscosity Index	D2270	140
Pour point, °C	D5950	-33
HTHS, cP @ 150 °C	D4683	4.2
Flash Point, COC,	D92	242
Cold Cranking Viscosity, cP @ -20 °C	D5293	4,790
MRV TP-1, cP @ -25 °C	D4684	15,700
Total Base Number (TBN), mg/g	D2896	6.5
Sulphated ash, mass %	D874	0.80
Zinc, mass %	D4951	0.088

The values quoted above are typical of normal production. They do not constitute a specification.

## Health and Safety

To obtain Material Health and Safety Data Sheets, contact one of Petro-Canada's TechData Info Lines.



## TechData Info Lines

To place an order, please call a Customer Order Management Representative at :

**Canada (English)** . . . . . Phone 1-800-268-5850  
**(French)** . . . . . Phone 1-800-576-1686  
**United States** . . . . . Phone 1-877-730-2369  
**Latin America** . . . . . Phone +1-416-730-2369  
**Europe** . . . . . Phone +1-416-730-2389  
**Asia** . . . . . Phone +1-416-730-2372  
**China** . . . . . Phone +86 (21) 6362-0066

To learn more about how Petro-Canada lubricants, specialty fluids, oils and greases can help maximize your equipment performance, savings and productivity, please contact us at :

**North America** . . . . . Phone 1-866-335-3369  
**Europe** . . . . . Phone +44 (0) 121-781-7264  
**Germany** . . . . . Phone +49 (0)201 726 2913  
**Latin America** . . . . . Phone +1-416-730-2369  
**Asia** . . . . . Phone +1-416-730-2372  
**China** . . . . . Phone +86 (21) 6362-0066  
**E-mail** . . . . . sales@suncor.com

You can also e-mail us at [lubecsr@suncor.com](mailto:lubecsr@suncor.com)

Visit us on the web at [lubricants.petro-canada.ca](http://lubricants.petro-canada.ca)

IM-8067E (2013.05)

Petro-Canada is a Suncor Energy business  
™Trademark of Suncor Energy Inc. Used under licence.

Beyond today's standards.



PRINTED IN CANADA ♻️ PRINTED ON RECYCLABLE PAPER